

Soldering Tips - Weller Compatible

C SERIES

COMPATIBLE STATIONS: Weller WTCPT, Weller WTCPTD, Weller WTCPTE, Weller WTCPN, Weller WTCPS, Weller TC201T, Weller TC201FE

Plato is one of the largest manufacturers of solder tips in the world, producing tips to fit all of the most popular solder stations. The long life and fast heat recovery of a Plato solder tip increases user effectiveness and decreases production times. All Plato solder tips manufactured since January 2004 are tinned with Lead-Free solder. Plato is the name for reliable soldering supplies.

Long Life: Using a high quality Plato solder tip increases solder speeds and decreases the total cost of manufacture. Higher temperatures and high tin content solders, common in lead-free solder processes, place additional strain on soldering iron tips. The long life of a Plato solder iron tip reduces tip changes, decreasing the total number of tips used and decreasing production time.

Rapid Heat Recovery: Plato solder tips are constructed from highly conductive premium grade copper to transmit heat to the work more quickly than other brands. This quick heat recovery enables more joints to be soldered per minute, thus reducing manufacturing time and costs.



- Fast heat recovering increases soldering speed
- Longer tip reduces manufacturing costs
- · Fewer tip change overs

Request More Info

Product Dimensions


C-3039-7 700°F screwdriver

Cross Reference: Weller PTA7, Weller PTR7

1.6mm

10 units/case






C-3039-8 800°F screwdriver

Cross Reference: Weller PTA8, Weller PTR8
1.6mm
10 units/case






C-3040-7 700°F screwdriver

Cross Reference: Weller PTB7 2.4mm 10 units/case






C-3040-8 800°F screwdriver

Cross Reference: Weller PTB8 2.4mm 10 units/case







C-3036-7 700°F screwdriver

Cross Reference: Weller PTC7

10 units/case





C-3036-8 800°F screwdriver

Cross Reference: Weller PTC8

3.2mm 10 units/case






C-3036-9 900°F screwdriver

Cross Reference: Weller PTC9

3.2mm 10 units/case





C-3100-7 700°F screwdriver

Cross Reference: Weller PTH7, Weller PTJ7

0.8mm 10 units/case



C-3100-8 800°F screwdriver

Cross Reference: Weller PTH8, Weller PTJ8

0.8mm





C-3043-7 700°F long screwdriver

Cross Reference: Weller PTK7

1.2mm



C-3043-8 800°F long screwdriver

Cross Reference: Weller PTK8

1.2mm

10 units/case



C-462-7 700°F conical

Cross Reference: Weller PTP7, Weller PTT7

0.8mm

10 units/case



C-462-8 800°F conical

Cross Reference: Weller PTP8

0.8mm 10 units/case



C-494-7 700°F long conical

Cross Reference: Weller PTS7

10 units/case





C-494-8 800°F long conical

Cross Reference: Weller PTS8, Weller PTT8
0.4mm
10 units/case



C-5141-7 700°F bevel

Cross Reference: Weller PTCC7, Weller PTDD7 3.2mm
10 units/case



C-5141-8 800°F bevel

Cross Reference: Weller PTCC8, Weller PTDD8 3.2mm 10 units/case





C-5141-9 900°F bevel

Cross Reference: Weller PTCC9, Weller PTDD9 3.2mm 10 units/case





North America

Techspray P.O. Box 949 Amarillo, TX 79105 800-858-4043

Email: tsales@techspray.com

Europe

ITW Contamination Control Saffierlaan 5 2132 VZ Hoofddorp The Netherlands +31 88 1307 400 Email: info@itw-cc.com

Countries Outside US

Call to locate a distributor in your country.

Important Notice to Purchaser/User: The information in this publication is based on tests that we believe are reliable. The results may vary due to differences in tests type and conditions. We recommend that each user evaluate the product to determine its suitability for the intended application. Conditions of use are outside our control and vary widely. Techspray's only obligation and your only solution is replacement of product that is shown to be defective when you receive it. In no case will Techspray be liable for any special, incidental, or consequential damages based on breach of warranty, negligence or any other theory.

© 2017 Illinois Tool Works